

BP464N

Add-on block 4P 63A 300mA AC S

Technische Merkmale

Architecture

Neutral position	right
Number of poles	4 P

Main electrical features

Rated operational voltage Ue	230 / 400 V
Frequency	50 Hz

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	300 mA
Rated current	63 A

Electric current / temperature

Rating current 40°C	63 A

Frequency

Frequency	50 Hz

Power

Total power loss under IN	7,9 W

Tripping

Protected against nuisance tripping	yes

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

Dimensions

Depth of installed product	9,2 cm
Height of installed product	7 cm
Width of installed product	3,5 cm

Installation, mounting

Tightening torque	2,9Nm
Type of top rail clip for modular devices	Plastic
Type of bottom rail clip for modular devices	NA
Top removability for modular devices	yes
Bottom removability for modular devices	no

Connection

Connection cross-sect. flexible conductor	16mm²
Connection cross-sect. rigid cable	25mm²

Settings

Rated fault current adjustable	no
Delay adjustable	no
Time delay of residual current	0,3 s

Standards

European directive WEEE	concerned

Safety

Protection index IP	IP20
Residual current type	AC SEL

Use conditions

Operating temperature	-5…40 °C
Altitude	2000 m
Air humidity protection	Execution I