

MU463A

MCB 4P 6kA C-63A 4M

Technische Merkmale

Architecture

Neutral position	not applicable
Number of protected poles	4
Number of poles	4 P
Type of pole	4 P
Fixing mode	Din-Rail
Curve	C

Functions

Concurrently switching N-neutral	no
Sealable	yes

Connectivity

Top connection alignement for modular devices	Aligned terminal
Bottom connection alignement for modular devices	Aligned terminal

Main electrical features

Rated short circuit breaking capacity Icn AC according IEC60898-1	6 kA
Rated operational voltage Ue	400 V
Type of supply voltage	AC
Frequency	50/60 Hz

Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	4000 V

Electric current

Rated current	63 A
Rated service breaking capacity Ics AC according IEC 60898-1	6 kA
min/maxi threshold value of the AC thermal operation	1,13 / 1,45 In
Magnetic regulating currrent	5 / 10 In
min/maxi threshold value of the DC magnetic operation	7 / 15 In
min/maxi threshold value of the DC thermal operation	1,13 / 1,45 In
Rated service breaking capacity Ics under 230V AC according IEC 60947-2	7,5 kA
Rated service breaking capacity Ics under 400V AC according IEC 60947-2	7,5 kA
Breaking capacity on 1 pole for IT 400V NF 60947-2	3 kA
Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1	6 kA
Rated short circuit breaking capacity Icn under 400V AC according IEC60898-1	6 kA
Rated service breaking capacity Ics AC according IEC 60947-2	75 %
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	10 kA
Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	10 kA
Rated service breaking capacity Ics under 230V AC according IEC 60898-1	6 kA
Rated service breaking capacity Ics under 400V AC according IEC 60898-1	6 kA

Electric current / temperature

Rating current -25°C	78,9 A
Rating current -20°C	77,6 A
Rating current -15°C	76,2 A
Rating current -10°C	74,9 A
Rating current -5°C	73,5 A
Rating current 0°C	72,1 A
Rating current 5°C	70,7 A
Rating current 10°C	69,2 A
Rating current 15°C	67,7 A
Rating current 20°C	66,2 A
Rating current 25°C	64,6 A
Rating current 30°C	63 A
Rating current 35°C	61,4 A
Rating current 40°C	59,7 A
Rating current 45°C	57,9 A
Rating current 50°C	56,1 A
Rating current 55°C	54,3 A
Rating current 60°C	52,4 A
Rating current 65°C	50,7 A
Rating current 70°C	48,9 A

Current correction factors

Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85
Correction factor of magnetic tripping with 100 Hz	1,1
Correction factor of magnetic tripping with 200 Hz	1,2
Correction factor of magnetic tripping with 400 Hz	1,5
Correction factor of magnetic tripping with 60 Hz	1

Frequency

Frequency	50 to 60 Hz

Power

Total power loss under IN	24,63 W
Power loss per pole at In	6,55 W

Endurance

Electric endurance in number of cycles	4000
Number of mechanical operations	20000

Dimensions

Depth of installed product	70 mm
Height of installed product	83 mm
Width of installed product	70 mm

Installation, mounting

Type of top connection for modular devices	with screw
Tightening torque	2,8Nm
Type of top rail clip for modular devices	NA
Type of bottom rail clip for modular devices	metallic
Type of Bottom Connection for modular devices	BIconnect
Top removability for modular devices	no
Bottom removability for modular devices	no
360° product mounting position	yes

Connection

Connection cross-sect. flexible conductor	1 / 25mm²
Connection cross-sect. rigid cable	1 / 35mm²
Connection cross-section of input and output with screws, for massive conductors	1 / 35 mm²
Connection cross section of access and exit with screws, for flexible conductor	1 / 25 mm²
Type of connection	with screw

Equipment

Quick connect	no
With transparent product label holder	no

Standards

Standard text	IEC 60898-1
European directive WEEE	concerned

Safety

Protection index IP	IP20

Use conditions

Operating temperature	-25…70 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I^2t	3
Altitude	2000 m
Air humidity protection	for all climates
Storage/transport temperature	-25…80 °C